

DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

Introducing the all-new **ALM3222 Fully Automatic Laminator**



The next generation in fully automatic laminating of digital prints, the all new ALM3222 offers many upgrades from the original ALM3220:

- Heated rollers for crystal clear, scratch-free laminations
- Micro adjustable side trimmers for precise flush cutting or the exact border encapsulation you desire
- Now handles up to 13" wide sheets (12.6" of film coverage)
- Built-in long mode operation for banner length prints
- 25% increase in speed over the ALM3220

What remains the same is the easy "green button" operation that provides virtually labor free laminated and trimmed sheets. Excellent adhesion to even the most difficult digital prints with the same ASAP adhesive films pioneered on the ALM3220.

www.drylam.com • P: 888-633-1973 • F: 866-473-0534
23220 W 84th Street • Shawnee, KS 66227

ALM3222 Fully Automatic Laminator



SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

ALM3222 Fully Automatic Laminator

Key Features:

- Small footprint - less than 4 sq. ft.
- Portable - locking roller casters
- 120 volt, 15 amp service with economy mode
- Ultra quick warm up of less than 5 minutes
- Virtually unattended operation
- Digital sheets sizes: 13"x19", 12"x18", 11"x17", 8.5"x11"
- Operating with built in long mode allows sheets of infinite length to be laminated
- Automatically feeds up to 200 sheets
- Laminates copy paper or as heavy as 130# cover stock
- Automatic two side lamination or short one side work
- Automatic flush or sealed edge trim option micro adjustable for precise flush cut or custom encapsulation
- 1 year parts and labor warranty

ALM Exclusive ASAP Roll Film

- Perfect for Digital Print technology
- Anti-static properties

1.5mil, 12.6" x 984 ft, Gloss	1.5mil, 12.6" x 984 ft, Matte
3.0mil, 12.6" x 492 ft, Gloss	3.0mil, 12.6" x 492 ft, Matte
5.0mil, 12.6" x 328 ft, Gloss	5.0mil, 12.6" x 328 ft, Matte
1.2mil, 12.6" x 984 ft, Nylon (Gloss & Matte versions)	



ALM Specifications

Model	ALM3222
Laminating Speed	20"-68"/min.
Temperature Range	170-270°F
Ultra Fast Warm-Up Time	Approximately 5 minutes
Film Thickness	1.2mil (One-sided application), 1.5mil, 3mil, 5mil ASAP Roll Film
Thickness of Objects	20lb bond - 130lb cover
Paper Feeding	Capacity: 200 Sheets, Adjustable Paper Guide
Applicable Sizes	Letter Paper Size: 8½" x 11" Tabloid Paper Size: 11" x 17" Digital Paper Paper Size: 12" x 18" Paper Paper Size: 13" x 19"
Trimming Methods	2 modes – Flush trim or edge seal for all 4 sides of the print
Operation Panel	LCD display for start, stop, temperature, speed, and trim settings, leading and trailing edge side cuts are adjustable
Other Features	Laminated sheet counter, Film tension control, Roller gap lever, Paper thickness adjustment lever, Automatic stop at end of film, Power saving mode, Emergency stop function
Power Consumption	900W
Power Supply	AC 120V (60Hz)
Net Weight	Laminator: 130 Lbs. Stand: 48.5 Lbs.
Included Accessories	Stand with film waste box, Printed operations manual



Mid-State Litho, Inc.
 5459 Fenton Rd., Flint, MI 48507
PH: 810.238.7370 | sales@midstatelitho.net